



FREQUENCY	118-136MHz
POLAR RADIATION	OMNI DIRECTIONAL
POLARISATION	VERTICAL
IMPEDANCE	50 OHMS
VSWR	<1.5:1 AT RESONANT POINT
BANDWIDTH	+/- 5% @ 2:1
GAIN	UNITY (OVER HALF WAVE DIPOLE)
CABLE	6M RG174 AS STANDARD
CONNECTOR	PL-259 AS STANDARD
POWER RATING	50W
ELEMENT	SOLID BRASS TAPE ELEMENT
MOUNTING	HOOK AND LOOP STRAPS
LENGTH	1.65m TOTAL LENGTH
DC GROUND	DC GROUNDED – THE ANTENNA WILL READ SHORTED ON CONTINUITY TEST
RECOMMENDED CARTRIDGE	16G THREADED CO2 CARTRIDGE

Coax Solutions Ltd Unit 11, Stort Mill Riverway Harlow, Essex, CM20 2SN 01279 639464	Stock Number INLF8-AIR BAND	
	<table border="1"> <tr> <td>Date 2 October 2019</td> <td>Rev 1</td> </tr> </table>	Date 2 October 2019
Date 2 October 2019	Rev 1	

Every effort is made to ensure the accuracy of the information provided on this data sheet. However coax Solutions Ltd accepts no liability for mis-application of this product as a result of errors, and may alter product design and specification without notice.